

LOVESHAW - Little David

H.) CHECK BLADE FOR SHARPNESS AND IF IT IS CLEAN. ALSO SHOULD HAVE A LITTLE MINERAL OIL ON IT.

F.) MAKE SURE THIS ROLLER MOVES FREELY IN BOTH DIRECTIONS AND THAT THERE ARE NO OLD TAPE PIECES.

END OF TAPE SHOULD BE POSITIONED AT MID-ROLLER. TOO LONG AND TENSION WILL BE TOO LOW. TOO SHORT AND TENSION WILL BE TOO HIGH.

G.) CHECK MAIN SPRING FOR TENSION - SHOULDN'T BE TOO WEAK. IF TOO WEAK, IT WILL NOT WIPE DOWN TAPE. IF TOO STRONG, IT WILL DE-FORM BOX.

E.) MAKE SURE ROLLER MOVES FREELY IN ONE DIRECTION ONLY AND THAT THERE ARE NO OLD TAPE PIECES.

D.) TAPE FINGER NEEDS TO BE TOUCHING TAPE. THIS GIVES TAPE STRENGTH TO STAND UP.

B.) TAPE ROLL BACKLASH ADJUSTMENT - ONLY ADJUST ENOUGH TO KEEP ROLL FROM BACKLASHING.

C.) TAPE TENSION ADJUSTMENT - NEED ONLY ENOUGH TENSION TO CUT TAPE. TOO MUCH AND TAPE WILL SNAP BACK ON ITSELF.

A.)**MAKESURE TAPE IS THREADED CORRECTLY**

